



**Capital Lighting Fixture Company**  
5359 Rafe Banks Drive, Flowery Branch, GA, 30542-2768  
TF: 800.323.3257 | P: 770.965.7238 | F: 770.965.7254  
www.capitallightingfixture.com



**Collection:** *Brookwood*

## 2 Light Outdoor Wall Fixture

9962BK

9"W x 18.75"H x 10.25"D

Black

### Specs

#### Description

2 Light Outdoor Wall Fixture

#### Collection

Brookwood

#### Finish Description

Black

#### Fixture Material

Cast Aluminum+Steel

#### Glass

Seeded Glass

#### Lamping

2-60 Watt Candelabra

#### Voltage

120V

#### Certification

UL Listed. Rated for Wet Environments.

#### Back Plate Junction Top

16.25"

#### Back Plate Length

12.63"

#### Back Plate Width

4.63"

#### Center/Top

12.38"

#### Center/Bottom

7"

---

**About**

Designed in Atlanta. Manufactured in China.

**Category**

Outdoor

**Style**

Traditional

**Light Source**

Incandescent

**Room List**

Exterior

Job Name:

Job Type:

Comments:

Quantity:

**OL5701BK: 2 - Light Wall Lantern**

**Dimensions:**

**Width:** 8"  
**Height:** 19 3/4"  
**Weight:** 4.73 lbs.

**Extends:** 11 1/4"

**Bulbs:**

2 - Candelabra A19 60w Max. 120v - Not included

**Features:**

**Material List:**

1 Body - Stainless Steel - Black  
1 Body - Aluminum - Black

**Safety Listing:**

Safety Listed for Wet Locations

**Instruction Sheets:**

English (OL5701)



**Collection:** Woodside Hills

**UPC #:** 014817318098

**Finish:** Black (BK)

**Backplate / Canopy Details:**

Type	Height / Length	Width	Depth	Diameter	Outlet Box Up	Outlet Box Down
Back Plate	9	4 1/2			6 1/2	13 1/4

**Shipping Information:**

Package Type	Product #	Quantity	UPC	Length	Width	Height	Cube	Weight	Fr. Class	UPS Ship
Individual	OL5701BK	1	014817318098	20.75	13.5	11	1.783	8.745	150	Yes
Master Pack	OL5701BK	2	10014817318095	20.75	13.5	22	3.566	17.49	150	Yes
NJ Pallet		42		48	40	70	77.778	367.29		No
NV Pallet		42		48	40	70	77.778	367.29		No



**8614891S-12: Medium LED Outdoor Wall Lantern**



**Collection:** Conroe

**UPC #:**785652108266

**Finish:** Black (12)

**Dimensions:**

**Width:** 7 3/16"

**Height:** 14 3/8"

**Extends:** 4 3/16"

**Wire:** 6" (color/Black/White)

**Mounting Proc.:** Center Lock-Up

**Connection:** Mounted To Box

**Bulb Type:** Modules

**Bulb Base:** Integrated

**Volts:** 120

**Watts:** 14

**Watts Consumed:** 14

**Watts Rated:** 14

**Hours Rated:** 50000

**Lumens:** 1000

**Bulb Temp:** 2700 °K

**CRI:** 90

**Features:**

- Advanced LED technology that warms in color when dimmed (2700K - 2200K).
- Meets Title 24 energy efficiency standards

**Material List:**

1 Body - Aluminum - Black

1 Cap - Aluminum - Black

**Safety Listing:**

Safety Listed for Wet Locations

**Instruction Sheets:**

Trilingual (English, Spanish, and French) (990W8\_14891S-CON)

**Shade / Glass / Diffuser Details:**

Part	Material	Finish	Quantity	Item Number	Length	Width	Height	Diameter	Fitter Diameter	Shade Top Length	Shade Top Width	Shade Top Diameter
Panel	Glass	Clear Seeded	1	G560234-67								
Panel	Glass	Clear Seeded	2	G560235-67		3 1/4	8 5/8					

**Backplate / Canopy Details:**

Type	Height / Length	Width	Depth	Diameter	Outlet Box Up	Outlet Box Down
Back Plate	9	7 3/16	5/8		9	5 3/8

**Shipping Information:**

Package Type	Product #	Quantity	UPC	Length	Width	Height	Cube	Weight	Fr. Class	UPS Ship
Individual	8614891S-12	1	785652108266	17.25	9.75	7	0.681	3.9	150	Yes
Master Pack	8614891S-12	4	10785652108263							
Shipping Master	8614891S-12	4	20785652108260	20	17.75	14.75	3.03	17.7	150	Yes

NJ Pallet		96		48	40	64	71.111	424.8		No
NV Pallet		96		48	40	64	71.111	424.8		No

# MINKA-LAVERY®

Item #: <b>71163-143C-L</b>	UPC Code: <b>747396097893</b>
Product Family Name: <b>Baytree Lane</b>	Finish: <b>Oil Rubbed Bronze W/Gold Highlights</b>
Category: <b>Wall Mount</b>	Category Type: <b>LED Outdoor</b>
Certification <b>3057374</b>	
Patents	
Notes:	



Image File Name:  
71163-143C-L--  
1456784632.jpg



## MEASUREMENTS

Width: <b>8.5</b>	Length: <b>8.5</b>	Height: <b>8.5</b>	Extension: <b>11.5</b>
Height Adjustable: <b>No</b>	Min Overall Height:	Max Overall Height:	Slope: <b>No</b>
Wire Length: <b>7"</b>	Chain Length:	Safety Cable Included: <b>No</b>	Net Weight: <b>1.30</b>
Canopy Width:	Canopy Height:	Canopy Length:	
Backplate Width: <b>5.00</b>	Backplate Height:	Center to Top: <b>4.88</b>	Center to Bottom: <b>3.50</b>

## SHADE / GLASS

Description:	Material: <b>Glass</b>
Part No.:	Quantity: <b>1</b>
Width: <b>3.35</b>	Height: <b>1.57</b>
	Length: <b>3.35</b>

## LAMPING

No. of Bulbs: <b>1</b>	Light Type: <b>Z18,Led</b>			
Max Bulb Wattage: <b>14</b>	Socket: <b>Y17,Led</b>			
Dimmable: <b>Yes</b>	Ballast:	Rated Life Hours: <b>30000</b>	Photocell Included: <b>N</b>	Lamps Included: <b>Yes</b>
LED Included: <b>Yes</b>	Color Temp.: <b>2700</b>	CRI: <b>90</b>	Initial Lumens: <b>980.000</b>	Delivered Lumens: <b>376.000</b>



## SHIPPING

Carton Width: <b>10.500</b>	Carton Height: <b>10.500</b>	Carton Length: <b>13.750</b>
Carton Weight: <b>3.010</b>	Carton Cubit Feet: <b>0.877</b>	Small Package Shippable: <b>Yes</b>
Master Pack Width:	Master Pack Height:	Master Pack Length:
Master Pack Weight:	Master Cubic Feet:	Multi-Pack:
		Master Pack: <b>1</b>

**LED**



LED

Dark Sky   Wet Location

ETL Intertek

Yes

Yes

Yes

Yes

# KICHLER

ARCHITECTURAL OUTDOOR

## Design Pro LED Accent 6.5W




16006 (6.5W 10° Spot) 16007 (6.5W 35° Flood) 16008 (6.5W 60° Wide Flood)

PROJECT:
TYPE:
ORDERING # :
COMMENTS:

### FEATURES

- Three beam spread options put light where you want it.
- A range of Kelvin color temperature choices from warm white 2,700K to pure white 3,000K.
- Radiax™ Optics deliver the greatest lumens per watt in the industry.
- Tight LED binning tolerances mean greater color consistency.
- Built-in adjustable cowl provides better glare control.
- 9V-15V operating range virtually eliminates voltage drop.



can be used in up or down position

### ORDERING INFORMATION



EXAMPLE: 16006 AZT27, 16060 AZT, 16064 AMB

Product ordered is a 6.5W, 2700K, 10 degree spot accent light in Textured Architectural Bronze with a long cowl and an amber lens accessory.

PRODUCT	WATTAGE/STYLE	LIGHT SOURCE	FINISH	OPTIONS / ACCESSORIES
<b>2700K WARM WHITE</b> 10 Degree 16006 AZT27 16006 BBR27 16006 BKT27 16006 BE27  35 Degree 16007 AZT27 16007 BBR27 16007 BKT27 16007 BE27 16007 WHT27  60 Degree 16008 AZT27 16008 BBR27 16008 BKT27 16008 BE27	*6.5W / 10VA - 10 Degree Spot Beam Spread  *6.5W / 10VA - 35 Degree Floodlight Beam Spread  *6.5W / 10VA - 60 Degree Wide Floodlight Beam Spread	<b>LED Specs</b> - Integrated LEDs & Driver - LEDs: High Output CREE® LEDs tightly binned for color uniformity - Color Temp. (CCT): 2,700K (-50/+100) Warm White 3,000K (-45/+130) Pure White - CRI: 80s - 9V-15V AC/DC - 40,000 Hours Lamp Life To L70 Specifications ** - Efficacy: 2,700K = 47Lm/W 3,000K = 54Lm/W  <b>Wiring</b> - 24" of Usable #18-2 Wire - SPT-1-W Leads  <b>Included Mounting Accessories</b> - 8" In-Ground Stake - Pro Series Wire Connector  <b>Note:</b> Fixture is Not For Use w/ Electronic Transformers	<b>Marine Grade Powdercoats</b> <b>Cast Aluminum</b> AZT - Textured Architectural Bronze  BKT - Textured Black  BE - Beach  WHT - White (Textured White only available in 35° beam)  <b>Cast Brass</b> BBR - Bronzed Brass	<b>Mounting Options</b> <b>Flange For Surface Mounting</b> 15601AZT - Textured Bronze Finish 15601BKT - Textured Black Finish 15601BBR - Bronzed Brass Finish  <b>Flange For Tree / Surface Mounting</b> 15607AZT - Textured Bronze Finish 15607BKT - Textured Black Finish 15607BBR - Bronzed Brass Finish 15607WHT - Textured White Finish  <b>90° Elbow</b> 15647AZT - Textured Bronze Finish 15647BKT - Textured Black Finish 15647BBR - Bronzed Brass Finish  <b>Junction Box Mounting Bracket</b> 15609AZT - Textured Bronze Finish 15609BKT - Textured Black Finish  1/2" NPSM thd.  1.18" W 2.09" H 1.35" L
<b>3000K PURE WHITE</b> 10 Degree 16006 AZT30 16006 BBR30 16006 BKT30 16006 BE30  35 Degree 16007 AZT30 16007 BBR30 16007 BKT30 16007 BE30 16007 WHT30  60 Degree 16008 AZT30 16008 BBR30 16008 BKT30 16008 BE30				<b>Lens Options</b>  16065AMB - Amber Lens For a Warmer Hue  16065FRO - Frosted Lens For Diffusing Light Where Needed  16065GRN - Green Lens For Intensifying Foliage Colors
				<b>Cowl Options</b> <b>Long Cowl</b> 16060AZT - Textured Bronze Finish 16060BBR - Bronzed Brass Finish 16060BKT - Textured Black Finish 16060WHT - Textured White Finish  <b>360° Cowl</b> 16061AZT - Textured Bronze Finish 16061BBT - Bronzed Brass Finish 16061BKT - Textured Black Finish 16061WHT - Textured White Finish     

PROJECT:
TYPE:
ORDERING # :
COMMENTS:

## PHOTOMETRIC INFORMATION

PRODUCT	DISTANCE	FOOTCANDLES	BEAM WIDTH	
10 Degree Spot 16006	8 Feet	106.3	1.6 Feet	 <p><b>Narrow Spot</b></p> <p><b>10 Degree Spread</b></p>
	12 Feet	48.4	2.4 Feet	
	24 Feet	12.2	4.8 Feet	
	36 Feet	5.4	7.2 Feet	
	48 Feet	3.1	9.6 Feet	
	60 Feet	2	12 Feet	
35 Degree Floodlight 16007	4 Feet	66.1	2.3 Feet	 <p><b>Flood</b></p> <p><b>35 Degree Spread</b></p>
	8 Feet	16.5	4.5 Feet	
	16 Feet	4.1	9.1 Feet	
	24 Feet	1.8	13.6 Feet	
	32 Feet	1	18.1 Feet	
	40 Feet	0.7	22.6 Feet	
60 Degree Wide Floodlight 16008	4 Feet	15	4.2 Feet	 <p><b>Wide Flood</b></p> <p><b>60 Degree Spread</b></p>
	8 Feet	3.7	8.5 Feet	
	16 Feet	0.9	17 Feet	
	24 Feet	0.4	25.5 Feet	
	32 Feet	0.2	34 Feet	
	40 Feet	0.2	42.4 Feet	

## NOTES

FCC  
Compliant

\*\*Definition of 40,000 hours: Voluntarily following the accepted industry standard of L70, Kichler rates the entire lighting fixture system at 40,000 hours; with engineered electronics that will last at least 40,000 hours, superior optical engineering, and finally utilizing a design that operates at the optimal temperature thresholds for the LED chips. The end result is a complete light fixture that does not require replacement parts and will provide 70% or more of its original light output for at least 40,000 hours. It has been proven that the human eye can hardly detect any difference in light output when light output is at 70% or above of its original output.



\* 6.5W is The Halogen Equivalent of a 35W MR16 Lamp  
 - Fixtures Must be Used With a Kichler ANSI/UL Power Supply  
 IES Files & LM-79 Data is available at [www.landscapelighting.com](http://www.landscapelighting.com).  
 LM-79 data is not available on our site.

We reserve the right to revise the design or components of any product due to parts availability or change in UL standards, without assuming any obligation or liability to modify any ANSI/UL Standards products previously manufactured, and without notice.