



21317 Hart St.
 Canoga Park, CA 91303
 Toll Free: 888-882-4823
 Email: sales@bestprolighting.com

SPECIFICATION SHEET

<p>BPL-100 Fixture Specifications:</p> <p>Housing: Die-cast aluminum</p> <p>Swivel: Die-cast aluminum swivel, with 1/2 NPT hub on bottom.</p> <p>Finish: Polyester UV powder coated, available in BLK- Black, RST-Rust.</p> <p>Socket: G4 socket.</p> <p>Lamp: 12V, JC Two Pin G4 halogen bulb 20W standard, 50W Max. LED lamps available in 3W, with 2700K white color temperature</p>	<p style="text-align: center;">•Directional Light •Aluminum</p> <p>Wiring: Fixture is prewired with a 3ft 18-2 direct burial cord. Silicone filled wire nut BPL-80 available from BestProLighting.com. Wire nuts sold separately.</p> <p>Mounting Spike: Black 3 1/2" ABS spike with 1/2" NPT male hub on top</p> <p>Electrical Notes: A 12V transformer is required. Options are available from BestProLighting.com. Voltage range for 12V halogen lamps are 11V-12.5V. Voltage range for LED lamps are 8V-21V. Proper grease/lubricant is suggested on threaded parts during installation process.</p> <p>Warranty: Limited five (5) year warranty on fixture housing and stem against manufacture's defects.</p>
---	--



AVAILABLE LED LAMPS						
LAMP NUMBER	WATTS	BEAM		COLOR & TEMP.	RATED HOURS	HALOGEN EQUIVALENT
		SPREAD	LUMEN			
3W04LED 3		360°	270	2700K	50000	20 Watt

AVAILABLE HALOGEN LAMPS					
LAMP NUMBER	WATTS	BEAM		COLOR & TEMP.	RATED HOURS
		SPREAD	LUMEN		
JC Bin Pin G4 10W	10	360°	75	2700K	2000
JC Bin Pin G4 20W	20	360°	150	2700K	2000
JC Bin Pin G4 35W	35	360°	265	2700K	2000
JC Bin Pin G4 50W	50	360°	400	2700K	2000

For additional lamps and accessories, visit bestprolighting.com

